

## MOISTURE-CURABLE ADHESIVE COMPOSITION

Publication number: JP7126600

Publication date: 1995-05-16

Inventor: KUDO KAZUSUKE; ZENKI YASUKAZU

Applicant: SEKISUI CHEMICAL CO LTD

Classification:

- international: C08G18/42; C09J175/00; C09J175/04; C08G18/42;  
C08G18/00; C09J175/00; C09J175/04; C08G18/00;  
(IPC1-7): C08G18/42; C09J175/04

- European:

Application number: JP19930271759 19931029

Priority number(s): JP19930271759 19931029

Report a data error here

### Abstract of JP7126600

**PURPOSE:**To obtain a moisture-curable adhesive compsn. with a very high curing speed and an excellent initial cohesive force by using a specified crystalline polyester polyol as a constituent of a urethane prepolymer prepolymer having isocyanate groups on its molecular terminals.

**CONSTITUTION:**In the adhesive compsn., a urethane prepolymer is formed by using a mixture of a polyester polyol A which is crystalline at ordinary temp. and a polyester polyol with a rosin skeleton in its molecule or a polyester polyol with a rosin skeleton in its molecule B, or a polyester polyol C which is crystalline at ordinary temp. and having a rosin skeleton in its molecule. The polyols A and C are prepd. by reacting a glycol having a molecular chain structure of  $-(CH_2)_n$  with a dicarboxylic acid having a molecular chain structure of  $-(CH_2)_m$ -and at least one of polyester polyols satisfying the conditions of  $14 \leq n+m$  or  $8 \leq n+m \leq 14$ .

---

Data supplied from the **esp@cenet** database - Worldwide